

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler



so many fake sites. this is the first one which worked! Many thanks

1-22 In Brief



2. Open the rear hatch, lift the load support floor covering (A), and remove the charge cord (B). It is located near the tire inflator and compressor kit (C). Pull up on the charge cord handle (D) to release it from the handle clip (E). Lift the charge cord up and forward to remove it from the vehicle. The vehicle plug (F) is stored as shown.
3. Plug the charge cord into the electrical outlet. See Electrical Requirements for Battery Charging on page 8-52. Verify that the charge cord status

Indicators are both green. See Charge Cord on page 8-60 for more information.



4. Then plug in the vehicle plug of the charge cord into the charge port on the vehicle. Verify that the charging status indicator illuminates on top of the instrument panel and a horn chirp occurs. See Charging Status Feedback on page 8-47 for more information.
5. To arm the charge cord theft alert, lock the vehicle with the RKE transmitter. To disable this

feature, see "Charge Cord Theft Alert" in Vehicle Personalization on page 8-53.

End Charge

1. Unlock the vehicle with the RKE transmitter to disarm the charge cord theft alert.
2. Unplug the vehicle plug of the charge cord from the vehicle by squeezing the vehicle plug lever and pull to remove.
3. Close the charge port door by pressing firmly in the center to latch properly.
4. Unplug the charge cord from the electrical outlet.

[Download PDF version of :](#)
2012 Chevy Volt Manual