

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler




so many fake sites. this is the first one which worked! Many thanks

2 2800

Rocker assemblies

Rocker shaft diameter (A2) 40.000 \pm 0.010 mm (1.5748 \pm 0.0004 in)
Valve rocker lever bore (A1) 40.200 \pm 0.010 mm (1.5774 \pm 0.0004 in)
Bearing clearance between valve rocker lever and shaft 0.040 to 0.060 mm (0.0016 to 0.0024 in)
Unit injector rocker lever bore (A3) 41.000 \pm 0.020 mm (1.6129 \pm 0.0008 in)
If a new bearing is fitted to the unit injector rocker lever, the oil hole in the bearing must be aligned with the oil passage in the rocker lever within 2,4 mm (0.09 in). The bearing must not extend beyond either face of the rocker lever.

Bore in the rocker lever bearing (A4) 40.000 \pm 0.010 mm (1.5748 \pm 0.0004 in)
Maximum permissible worn dimension 40.191 (1.5824 in)



[Download PDF version of :](#)
2800 Perkins Engine Workshop Manual