

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler



so many fake sites. this is the first one which worked! Many thanks

[Download PDF version of :](#)
Honda Recon Service Manual

REAR DRIVING MECHANISM

Replace the pinion shim with a thicker one if the contact pattern is too high, toward the face.
Replace the pinion shim with a thinner one if the contact pattern is too low, toward the flank.
The pattern will shift about 0.5 - 1.0 mm (0.02 - 0.04 in) when the thickness of the shim is changed by 0.12 mm (0.005 in).

Pinion shim:

A: 1.64 mm (0.064 in)	F: 1.94 mm (0.076 in)
B: 1.76 mm (0.069 in)	G: 2.05 mm (0.079 in)
C: 1.78 mm (0.069 in)	H: 2.09 mm (0.081 in)
D: 1.82 mm (0.071 in)	I: 2.12 mm (0.083 in)
E: 1.88 mm (0.074 in)	J: 2.19 mm (0.086 in)

See page 10-11 for pinion gear removal and see page 10-12 for pinion shim replacement.

DRIVE PINION REMOVAL

Remove the O-ring.
Remove the oil seal.

Be careful not to damage the pinion gear teeth. Do not use a screwdriver or other sharp tool to pry the pinion gear out of the housing.

Unscrew the pinion bearing lock nut with a drill or impact driver.