

Download File PDF How To Adjust The Valves On A 17 Horsepower Briggs And Stratton Engine

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler




so many fake sites. this is the first one which worked! Many thanks

OHV Twin (Non Vanguard)

ADJUST VALVES


1. Set No. 1 cylinder at 114° (6.4mm) past TDC, compression stroke.
 - a. Adjust valves and check, Fig. 25.
2. Set No. 2 cylinder at 114° (6.4mm) past TDC, compression stroke.
 - a. Repeat for No. 2 cylinder.



Vanguard

Valve Clearance Adjustment

1. Set No. 1 cylinder at 114° (6 mm) past TDC, compression stroke.
2. Use a feeler gauge (1) to measure the valve clearance. Valve clearance should be 0.005" (0.13 mm) for the intake and exhaust valve.
NOTE: Measure valve clearance with the engine COLD.
3. If the valve clearance requires adjustment, loosen the lock nut (2) with a wrench (4). Use a hex wrench (5) to turn the adjusting screw (3) to adjust the valves, Fig. 48.
4. With the valve clearance correctly adjusted, hold the adjusting screw. Torque the lock nut to 70 in. lbs. (8 Nm).
5. Repeat for No. 2 cylinder.



[Download PDF version of :](#)

[**How To Adjust The Valves On A 17 Horsepower Briggs And Stratton Engine**](#)