

Download File PDF Maple 13 User Manual

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler



so many fake sites. this is the first one which worked! Many thanks

[Download PDF version of :](#)
Maple 13 User Manual

Config > Simple Project 47

Downloading your first project
First, connect a 24-VDC power supply to the HMI. Refer to the **HMS5000 Series Installation Guide** for more information.
In order to download your project, you must first connect the HMI to your computer. There are two methods of downloading to the HMI: Ethernet or USB, depending on your model.

Configuration Wiring

HMI Model	Ethernet Crossover Configuration Cable P/N: N411-0204	USB Configuration Cable P/N: N411-0215
HMS5007H, HMS5008, HMS5070H, HMS5100H		X
HMS5070H, HMS5007, HMS5047H	X	X
HMS5047, HMS5047H, HMS5112H, HMS5100K	X	

Ethernet
It is necessary to determine the IP Address of the HMI. By default, the HMI is configured to get a dynamic IP address from a DHCP server. This setting can be changed. To determine or change the HMI's IP address:

1. Plug a USB mouse into the HMI.
2. Connect the HMI to your computer using an Ethernet crossover cable (P/N: N411-0196).
3. Move the mouse pointer to the lower right corner of the HMI screen. A menu bar will appear. Click the wrench icon on the menu bar.
4. On the **Network** tab of the System Settings dialog, the HMI's IP address will be shown. If set for Auto Get IP address, the HMI's current IP range information is displayed but is not changeable. To change the IP address, select IP Address Get From Below and enter the data.
5. Once the IP Address has been established, the project can be downloaded. Select **Tools > Download** from the Distribution menu bar (or the Download icon).
6. Enter the HMI's IP address and Download password. The default download password is 111111. The default IP address is 192.168.0.201, Subnet: 255.255.255.0, Gateway (none).
7. Make sure that the **Ethernet**, **Firmware**, and **Reboot HMI After Download** boxes are checked.
8. Click the **Download** button. If the HMI is properly connected to the PC, the status box on the download dialog will update with messages indicating the progress of the transfer. The HMI itself will also display messages reflecting its status.
9. When the download is complete, the HMI will restart and will begin running your project. Click the **Exit** button on the Download dialog.

USB

1. Make sure the USB driver has been installed on your computer. See the Help menu "How Do I...Install the Maple Systems USB Driver" for more information.

100-1007, Rev. 10