

# Download File PDF Maruti Omni Repair Manual

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler



so many fake sites. this is the first one which worked! Many thanks

ORDER NO. H48661000

## Service Manual

Stereo Integrated Amplifier  
Amplifier  
SU-X950

Color:  Black  Silver

Area	Area
(K1)	..... Caribbean/Cayman
(K2)	..... Finland
(K3)	..... Australia
(K4)	..... Asia, Latin America, Middle East, Caribbean and Oceania
(K5)	..... Europe, Singapore, Hong Kong
(K6)	..... Belgium
(K7)	..... France
(K8)	..... F.R.Germany
(K9)	..... Italy
(K0)	..... Saudi Arabia

**SPECIFICATIONS**  
(SFR-41 500)

**■ AMPLIFIER SECTION**

Power output (1 kHz, THD 1%)	2 x 60 W (30%)
Total harmonic distortion (rated power at 1 kHz)	1% (50)
Frequency characteristic	10 Hz - 20 kHz
SN ratio at 1 kHz	60 dB (A, 1%)
Separation of tone and noise	52 dB
Dynamic range	30 dB
Input impedance and capacitance	10 kΩ ± 5%
PHONO	100 mV ± 5%
TUNING RANGE (1/TUNE)	530 - 16.2 MHz
CG/ANT	200 mV ± 5%
Power supply	100 VAC
Size (incl. power BT)	75 (W) x 110 (H) x 110 (D) mm
WEIGHT	1.2 kg
TUNING COIL CAPACITANCE (1/TUNE)	82 pF (ANT), 82 pF (CG)

**Frequency response**

FRQA Standard 2-tone	10 Hz - 20 kHz ± 0.5 dB
FRQB	10 Hz - 20 kHz ± 0.5 dB
FRQC	10 Hz - 20 kHz ± 0.5 dB
FRQD	10 Hz - 20 kHz ± 0.5 dB
FRQE	10 Hz - 20 kHz ± 0.5 dB

**■ GENERAL**

Power consumption	200 W
Power supply	100 VAC
For Japan, Singapore and Australia	AC 50/60 Hz, 230V
For continental Europe	AC 50/60 Hz, 230V
For Africa	AC 50/60 Hz, 230V
For America (N & S)	AC 50/60 Hz, 120V
Dimensions (W x H x D)	(145 x 110 x 110) mm
Weight	1.2 kg (2.65 lb)

**Notes:**  
1 Specifications are subject to change without notice.  
2 Specifications are subject to change without notice.  
3 True frequency distortion is measured by the digital spectrum analyzer (DF) 3000 system.

**Technics**  
Matsushita Electric Industrial Co., Ltd.  
Central P.O. Box 288, Osaka 550-96, Japan

[Download PDF version of :](#)  
[Maruti Omni Repair Manual](#)