

# Download File PDF Maruti Omni Service Manual

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler



so many fake sites. this is the first one which worked! Many thanks

ORDER NO. HA88610200

## Service Manual

Stereo Integrated Amplifier  
Amplifier  
SU-X950

Color:  Black  Black Type

Area	
Color	Area
(R)	..... Caribbean/Caribbean
(R)	..... Finland
(R)	..... Australia
(R)	..... Asia, Latin America, Middle East, Caribbean and Oceania
(R)	..... Europe, Singapore, and Oceania
(R)	..... Belgium, France, Germany, Italy, Spain, Portugal, and Greece
(R)	..... Japan
(R)	..... Saudi Arabia

**SPECIFICATIONS**  
(SFR-41 505)

**■ AMPLIFIER SECTION**

Dist. power output	2 x 65 W (30%)	Min. noise	100 dB
T.H.D. (1 kHz)	1%	Dist. noise	70 Hz - 10 kHz
Total harmonic distortion	0.02% (1 kHz)	Dist. noise	100 Hz - 10 kHz
Rated power at 1 kHz	170 W	TAPE 1 TAPE 2 REC OUT	100 mV
Maximum distortion	0.02% (1 kHz)	Compact disc (CD) 200 Hz - 6,300 Hz	1.0 V
Max. power at 1 kHz	1,000 W (100%)	Compact disc (CD) 200 Hz - 6,300 Hz	1.0 V
Rated load and source	16 Ω, 160 W	Headphone output level and impedance	333 mV (16 Ω)
Dynamic range	80 dB	Load impedance	16 Ω - 16 Ω
Input impedance and impedance	30,000 Ω	Min. input impedance	100 Ω
PHONO	30,000 Ω	MINI CD	100 Ω
TUNER input impedance (1 kHz, RMS)	200 Ω (100 Ω)	■ GENERAL	
CD-DA1	200 Ω (100 Ω)	Power consumption	200 W
Power	100 W	Power supply	For Japan, Singapore and Australia AC 50/60 Hz 200V
Size (incl. panel) (W x H x D)	75 x 98 x 170 mm	For Singapore, Malaysia and Indonesia AC 50/60 Hz 200V	
PHONO	82 x 98 x 170 mm	For other countries AC 50/60 Hz 200V	
TUNER CD-AUX TAPE 1 TAPE 2	82 x 98 x 170 mm	Dimensions (W x H x D)	(145 x 98 x 170 mm)
Frequency response	FLAA Standard 2 Line 6.0-20,000 Hz ± 1% (1 kHz)	Weight	6.0 kg (13.5 lb)
PHONO	FLAA Standard 2 Line 6.0-20,000 Hz ± 1% (1 kHz)		
TUNER CD-AUX TAPE 1 TAPE 2	15 Hz - 22 kHz ± 3 dB		
Dist. capacity	20 Hz - 15 kHz ± 10 dB		
Dist. THD	10 Hz - 15 kHz ± 10 dB		

**Notes:**  
1 Specifications are subject to change without notice.  
2 Total harmonic distortion is measured by the digital spectrum analyzer (DF-380) system.

**Technics** Matsushita Electric Industrial Co., Ltd.  
Central P.O. Box 289, Osaka 550-96, Japan

[Download PDF version of :](#)  
**Maruti Omni Service Manual**