

## #Jenny



Finally I get this ebook, thanks for all these I can get now!

## #Rio



Cool! I'am really happy

## #Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

## #Hun Tsu



wtf this great ebook for free?!

## #Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

## #Diego Butler



so many fake sites. this is the first one which worked! Many thanks

**LiftMaster** SMART CONTROL PANEL<sup>®</sup>  
MODEL 900LM

For use with LiftMaster 1/2" Garage Door Openers. All SmartCode 1/2" Garage Door Openers have a yellow Learn button and two yellow antennas. The buttons are adjustable and may be turned off or on as desired. Refer to the buttons settings section.

### Feature Overview

**SCREEN**  
The screen will display the time and temperature and the remote buttons is present, and then will display the remote options. There is a problem with the garage door opener the screen will display the Diagnostic Code.

**LIGHT BUTTON**  
Press the LIGHT button to turn the garage door opener lights on or off. After the lights are turned on they will stay on until the LIGHT button is pressed again, or until the garage door opener is activated. Once the garage door opener is activated the lights will turn off after the specified period of time (the factory setting is 45 seconds). The LIGHT button will control the lights when the door is in motion. The location of the light timing can be adjusted by accessing the menu using the navigation buttons.

**NOTIFY BEHAVIOR**  
The motion sensor will automatically turn on the garage door opener lights when motion is detected. The lights will come on for the set period of time, then shut off. The factory setting is on and set at 45 seconds.

**LINK**  
The 900LM is designed to prevent activation of the garage door opener from remote controls which are allowing activation from the open control and keypad entry. This feature is useful for added peace of mind when the home is empty (i.e. vacation).

**TIMER TO CLOSE (TTC)**  
The 900LM remote TTC is available on one door. TTC is for use with 900LM with wireless doors. Factory default is off. TTC will be set to automatically close your garage door from the fully open position after a specified period of time (1, 3, 5, 10 minutes) in a custom setting up to 90 minutes. The garage door opener will beep and the lights will flash when the timer starts. The timer on the door opener can display the status of the TTC. TTC WILL NOT work if the garage door opener is operating by battery power or if the safety reversing sensors are misaligned. This feature is NOT intended to be the primary method of closing the door. A keypad entry should be installed in the event of a disconnected link when using the feature.

**SMARTPHONE ALERT SYSTEM (SAS)**  
This feature alerts the homeowner in monitoring the garage door opener system stays in good working condition. A maintenance alert message will display on the screen indicating the garage door opener may be in need of maintenance. The SAS feature MUST be activated at time of installation. The factory setting is off.

**WARNING**

- To prevent possible DAMAGE ALARM or SAFETY from electrocution.
- Be sure power is NOT connected BEFORE installing door opener.
- Connect 900LM to 120VAC line voltage wires.
- To prevent possible DAMAGE ALARM or SAFETY from a closing garage door:
  - Install door opener within sight of garage door, out of reach of children at a minimum height of 5 feet (1.5m), and away from the closing path of door.
  - NEVER permit children to operate or play with door control push buttons or remote control accessories.
  - Activate door SENS when it can be seen clearly, is properly identified, and there are no obstructions in door travel.
  - Always keep garage door in sight until completely closed. NEVER permit anyone to cross path of closing garage door.

[Download PDF version of :](#)  
**Smart Manual**